APL ES BAS BLK

APPEAL Tap Range Appeal Eco Start Basin Mixer with Clicker Waste Black



Features:

- Eco Start technology saves energy by having cold water as the default central start position of the tap handle. Hot water is only activated when the tap lever is moved from the central position, so your boiler is not unnecessarily fired up.
- This tap has a flow regulator, which limits the flow of water to 5 litres per minute, reducing the amount of water you use.
- Long life ceramic cartridge for added durability and smooth control.
- Everything you need in the box including flexible tails and clicker waste so nothing to buy separately.
- On-trend matt black finish to make a statement in your bathroom or WC.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in chrome and brushed brass.
- Co-ordinating Bathroom taps available.


Product Certifications:

WRAS Certificate No: 2309904

WRAS

APPROVED PRODUCT

Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Paddle Lever			
Connection Inlet:	1/2" BSP Flexible Tails			
Connection Outlet:	Housed 5lpm M24 Aerator			
Number of Tap Holes:	1			
Valve/Cartridge Type:	35mm Cold Start Upper Seal Cartridge			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.5 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			



WRAS Expiry Date: 30/09/2028	Flow Rates (l/min)						
Water Label	System Pressure (bar)	0.5	0.5	1	2	3	5
	APL ES BAS BLK (mixed)	0.2	2.8	4.1	5	4.7	4.7
TECHNICAL DATA SHEET	B QUALLA S QUALLA VEARS PAR		В	RIS	ST	AN	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.