TAN BSM C

TANGRAM Tap Range

Tangram Bath Shower
Mixer Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Flick Up			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M24 Recessed Honeycomb Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.3 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black and brushed brass.
- Co-ordinating Bathroom taps available.

Dimensions (measurements in mm) 145 100 225 45 65 180 90 70 30

Product Certifications:





Kiwa Certificate No: 2312721 Kiwa Expiry Date: 12/12/2028

WRAS Certificate No: 2312358 WRAS Expiry Date: 31/12/2028





Flow Rates (I/min)								
System Pressure (bar)	0.3	0.5	1	2	3	5		
Through Bath Filler (mixed)	11.3	15.2	23	34	41.9	54.1		
Through Handset (mixed)	4	5.3	8.1	12	15.2	20.3		

TECHNICAL DATA SHEET



