ZI SHXDIVSMFF C

ZING Shower Range

Zing2 Adjustable Thermostatic Rigid Riser Diverter Bar Shower Chrome



Features:

- All in one box pack includes bar shower valve, hose, telescopic rigid riser rail and rub-clean anti-limescale drench head and single function handset so nothing to buy separately.
- Supplied with Bristan's Wall Mount 10 fast fixing kit for easier retro installation.
- Telescopic riser so you can adjust the height to suit your space. Giving you the flexibility to fit in a wet room/walk in shower or over a bath.
- Integral two outlet diverter so you can easily switch between the handset or drench head.
- Rub clean handset and drench head - limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.

Product Certifications:




WRAS Certificate No: 240203003 WRAS Expiry Date: 28/02/2029





Specification				
Finish/Colour:	Chrome Plated			
Main Construction Material:	ABS; Stainless Steel			
No of Controls:	2			
Shower Type:	Bar Shower			
Shower Head Type:	Fixed Head and Single Function Handset			
Shower Kit:	Telescopic Riser with Fixed Head			
Valve/Cartridge Type:	Thermostatic Cartridge			
Maximum Hot Water Supply Temperature °C:	60			
Plumbing System Suitability:	Suitable for all plumbing systems, ideally balanced			
Minimum Dynamic Pressure (bar):	0.5			
Maximum Dynamic Pressure (bar):	5			
Maximum Static Pressure (bar):	10			
Connection Inlet:	1/2" Compression			
Connection Outlet:	G1/2" and Riser Outlet			
Isolation Valve Included:	No			
Check Valve Included:	Yes			



Flow Rates (I/min)					
System Pressure (bar)	0.5	1	2	3	5
Through Handset (mixed)	3.9	6.4	10	12.4	16.6
Through Fixed Head (mixed)	5.8	8.6	12.5	15.5	20.2





BRISTAN

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

*- Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.