QB SHXDIVCTFF BLK

QUBO Shower Range Qubo Safe Touch Thermostatic Rigid Riser Diverter Bar Shower Black



Features:

- All in one box pack includes bar shower valve, hose, telescopic rigid riser rail and rub-clean anti-limescale drench head and multi function handset so nothing to buy separately.
- Supplied with a fast fit Wallmount 12 fixing kit with built-in front of wall isolation valves on both the hot and cold feed, making it simple to fit, maintain and replace.
- Safe Touch technology ensures the valve stays cool to the touch while in use.
- Telescopic riser so you can adjust the height to suit your space. Giving you the flexibility to fit in a wet room/walk in shower or over a bath.
- Integral two outlet diverter so you can easily switch between the handset or drench head.


Product Certifications:



WRAS Certificate No.: 240903006 WRAS Expiry Date: 31/09/2029

Specification					
Finish/Colour:	Black				
Main Construction Material:	Brass; Stainless Steel; ABS				
No of Controls:	2				
Shower Type:	Bar Shower				
Shower Head Type:	Fixed Head and Multi-Function Handset				
Shower Kit:	Telescopic Riser with Fixed Head and Handset				
Valve/Cartridge Type:	Thermostatic Cartridge				
Maximum Hot Water Supply Temperature ^o C:	60				
Plumbing System Suitability:	Suitable for high pressure plumbing systems				
Minimum Dynamic Pressure (bar):	1				
Maximum Dynamic Pressure (bar):	5				
Maximum Static Pressure (bar):	10				
Connection Inlet:	15mm Compression				
Connection Outlet:	G1/2"				
Isolation Valve Included:	Yes				
Check Valve Included:	Yes				

Dimensions (measurements in mm)



		Flow Rates (I/min)					
		System Pressure (bar)	1	2	3	4	5
Water Label	• 9.8 l/min	Through Handset (mixed)	4.3	6.3	7.6	8.3	8.3
		Through Fixed Head (mixed)	6.1	8.6	9.8	9.9	9.4







D2

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. * - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.